

# SBB monitors Swiss railways with imc measurement systems

Application area: rail > stationary > monitoring



The SBB has developed stationary **wheel-load checkpoints** that can automatically acquire key data from a passing train in real time. With the help from imc, these checkpoints are equipped with high-precision strain gauge bridge amplifiers, as well as an industrial PC according to customer specifications.

The system is designed to acquire **safety-relevant load data**, such as axle overloading and cargo shifting. It also recognizes **flat spots on the wheels**.

The measurement data is analyzed in real time and – if necessary – steps are taken to ensure safer and more secure railway travel. For example, trains can be instructed to slow down or even stop completely. In addition, condition-based maintenance can be arranged.

Questi prodotti sono distribuiti e supportati in Italia da:

Instrumentation Devices Srl Via Acquanera 29 - 22100 COMO (Italy) ph +39 031 525 391- fax +39 031 507 984 info@instrumentation.it - www.instrumentation.it

### The goal: safer railways

Rail traffic is generally very safe. But when problems do occur, there can be a lot at stake - from massive damage to loss of life.

Railway companies are therefore investing heavily in technical security measures to ensure the safe and efficient operation. The ideal railway monitoring system:

- runs 24 hours a day, 7 days a week
- works in real time
- is largely automated
- reliably detects technical problems before they turn into dangerous situations.

Through an extensive and close-knit network, stationary measurement systems attached directly to the train track measure relevant physical characteristics of passing trains travelling at normal operating speeds. The measurement data is then transmitted directly to the control room and evaluated. If there are relevant deficiencies detected, immediate action is taken – for example, trains will need to slow down or stop.



This automated railway monitoring system in Switzerland has been consistently expanded, developed and networked by SBB.

### Part 1: wheel-load checkpoints

Essential parts of this expansion are the wheel load checkpoints. Safety-critical load data are acquired and controlled as:

- the maximal permissible axle load
- the maximal permissible right/left load ratio (unbalanced load)
- deviation from the declared overall weight

The wheel-load checkpoints developed by the SBB are equipped with strain gauges attached to the left and right sides of the track and are connected to the imc CRONOS*flex* modular measurement system. It is set up with two 8-channel bridge amplifiers and a universal amplifier for acquiring temperatures.



imc CRONOSflex measurement system

The fully synchronous measurement within the device and its complex real-time signal processing qualify this imc measurement system to be used for an operation that monitors safety.

The measurement system acquires data to detect:

- load shifting
- axle overloading
- flat spots on the wheels

From the integrated real-time signal analysis performed in the device itself to the calculation of complex variables, the acquired primary data are thus reduced, by compressing and enriching, in terms of their complex "informational content".

#### Part 2: the overall system

Because of the multiple networking and communication possibilities, the wheel load checkpoints can be easily and comfortably integrated into the existing overall railway monitoring system. In this way, the SBB currently has 20 wheel-load checkpoints set up in Switzerland.

Another benefit to the SBB is that the overall development and maintenance of the system are taken care of by only two partners. The measurement hardware, including the IT component, is completely overseen by imc and the software side by a secondary partner of the SBB. This ensures effective communication and fast response times.

## Conclusion

The SBB operates 20 wheel-load checkpoints that allow for automated monitoring of all the trains on the Swiss rail network. The quality of the primary acquired measurement signals – for example with resolution, precision and bandwidth – could be improved over previously used methods using imc measurement technology: the achieved resolution, for example, is improved tenfold. As a result, a more accurate diagnosis can be provided, thus, increasing the quality of the available information.

The goal was achieved: The trains are safer, have fewer breakdowns and save time and money for the SBB and their customers.

Limiting the responsibility for the entire system to just two partners resulted in effective implementation with shorter reaction times.

© Fotos SBB

## **Technical Realization**

- imc CRONOS*flex* PC independent, decentralized, distributable measurement system with direct online analysis of measurement data.
- Software integration via imc DEVICES and imc COM
- Measurement PC; custom-made according to customer specifications
- 20 nodal points
- Each nodal point:
  - o imc CRONOS*flex*
  - Two 8-channel strain gauge bridge amplifiers
  - One universal measurement amplifier for temperature acquisition



# Additional information:

#### imc Meßsysteme GmbH

Voltastr. 5 13355 Berlin, Germany

Telephone:	+49 (0)30-46 7090-0
Fax:	+49 (0)30-46 31 576
E-Mail:	hotline@imc-berlin.de
Internet:	www.imc-berlin.com

For over 20 years, imc Meßsysteme GmbH has been developing, manufacturing and selling hardware and software solutions worldwide in the field of physical measurement technology. Whether in a vehicle, on a test bench or monitoring plants and machinery - data acquisition with imc systems is considered productive, user-friendly and profitable. So whether needed in research, development, testing or commissioning, imc offers complete turnkey solutions, as well as standardized measurement devices and software products. imc measurement systems work in mechanical and mechatronic applications offering up to 100 kHz per channel with most popular sensors for measuring physical quantities, such as pressure, force, speed, vibration, noise, temperature, voltage or current. The spectrum of imc measurement products and services ranges from simple data recording via integrated real-time calculations, to the integration of models and complete automation of test benches.

Founded in 1988 and headquartered in Berlin, imc Meßsysteme GmbH employs around 160 employees who are continuously working hard to further develop the product portfolio. Internationally, imc products are distributed and sold through our 25 partner companies.

#### imc Test & Measurement GmbH

Max-Planck-Str. 22 b 61381 Friedrichsdorf, Germany

Telephone:	+49 (0)6172 59675-0
Fax:	+49 (0)6172-5967-222
E-Mail:	hotline@imc-frankfurt.de
Internet:	www.imc-frankfurt.de

imc Test & Measurement GmbH is a system house that offers products and services for measurement applications. Our team of about 40 proven experts, having mainly backgrounds in engineering or science, work to realize customer-oriented and application-specific solutions on the subject of "electrical measurement of physical quantities."

imc Test & Measurement GmbH markets the recognizably innovative and powerful hardware and software products from their strategic partner, imc Meßsysteme GmbH, Berlin.

We complement these products with our comprehensive engineering services. These range from design, consulting and sales, with pre-and aftersales service, as well as customer and applicationspecific extensions, system integration, commissioning, training, rental of measuring systems, personnel contracting and much more.

#### Terms of use:

This document is copyrighted. All rights are reserved. Without permission, the document may not be edited, modified or altered in any way. Publishing and reproducing this document is expressly permitted. If published, we ask that the name of the company and a link to the homepage <u>www.imc-berlin.com</u> are included.

Despite careful preparation of the content, this document may contain errors. Should you notice any incorrect information, we ask you to please inform us at <u>marketing@imc-berlin.de</u>. Liability for the accuracy of the information is excluded.



